

# MIC1-400 public address

## A&E Specifications – version 1.0

### MIC1-400 public address fully functional PTZ camera

#### 18x camera version

The fully functional PTZ camera shall be a MIC1-400 PTZ camera rated to IP68 / NEMA 4x with a high resolution 18x true day/night camera and built-in twin public address speakers.

#### 36x camera version

The fully functional PTZ camera shall be a MIC1-400 PTZ camera rated to IP68 / NEMA 4x with a high resolution 36x true day/night camera and built-in twin public address speakers.

#### 1.0 The physical attributes of the unit shall meet the following design and performance specifications:

- 1.1 The unit shall be environmentally rated to IP68 / NEMA 4x with speakers rated to IP67
- 1.2 The unit shall operate from +50 degrees\* to -20 degree centigrade temperature variations, up to hurricane force wind conditions (above 120mph winds)
- 1.3 The unit shall be machined from 6mm thick solid aluminium
- 1.4 The unit shall be classed as vandal resistant
- 1.5 The unit shall have a weather resistant coating in a choice of colours:
  - 1.5.1 The unit shall be black (RAL9005)
  - 1.5.2 The unit shall be white (RAL9003)
  - 1.5.3 The unit shall be grey (RAL7001)
  - 1.5.4 The unit shall be available in bespoke RAL colours if pre-agreed minimum quantity levels are reached
- 1.6 The unit shall have the ability to be mounted either upright, inverted or canted at 45°
- 1.7 The unit shall be no more than 6.5kg with twin public address speakers fitted
- 1.8 The unit shall comply with ROHS, CE and FCC standards
- 1.9 The unit shall have dimensions of 205(W) x 420(H) x 162(D)mm with twin public address speakers fitted
- 1.10 The unit shall feature an optically perfect, flat viewing window
- 1.11 All weatherproof seals within the unit shall last for the 3yr warranty period of the unit without need for maintenance or replacement
- 1.12 To facilitate installation the unit shall be supplied with attached 4 inch PCD base as standard with pre-drilled hole suitable for a safety chain
- 1.13 The unit shall be capable of full operation at a composite cable length of 25 metres maximum between PTZ camera head and the power supply

\* Forward Vision recommends the use of a camera finished in white and using a sunshield in extremely sunny environments.

#### 2.0 The unit's high speed pan/tilt drive unit shall meet or exceed the following design and performance specifications:

- 2.1 The unit shall feature precision brushless motor technology for its pan/tilt drive
- 2.2 The pan/tilt drive speed shall range from 0.2° per second to 90° per second
- 2.3 The unit shall be capable of 360° continuous rotation pan and 320° tilt
- 2.4 The unit shall utilise resolver positioning technology
- 2.5 The unit shall have a pan and tilt position accuracy of greater than 0.08°

**3.0 The connectivity of the unit shall meet the following design and performance specifications:**

- 3.1 Video, power and telemetry shall be supplied to the unit through Forward Vision's multi-connector via a single cable

**4.0 The camera module within the PTZ unit shall meet or exceed the following design and performance specifications:**

**18x camera module**

- 4.1 The camera module shall feature a 1/4" EXview™ CCD  
4.2 The camera module shall be a true day/night unit  
4.3 The camera module shall switch from day mode (colour) to night mode (monochrome) via a photocell integrated into the PTZ camera head that can be set to user selectable levels, or via the remote keyboard.  
4.4 The camera module shall have a resolution of 470TVL (NTSC) / 460TVL (PAL)  
4.5 The camera module shall have an 18x optical zoom with 12x digital zoom  
4.6 The camera module shall have a minimum illumination sensitivity of 0.7 lux (F1.4, 1/60s NTSC, 1/50s PAL), 0.11 lux (F1.4, 1/4s NTSC, 1/3s PAL), 0.01 lux or less (F1.4, 1/4s NTSC, 1/3s PAL, ICR ON)  
4.7 The camera module shall have selectable on/off Backlight Compensation (BLC)  
4.8 The camera module shall have 16 steps aperture control  
4.9 The camera module shall have Automatic Gain Control (AGC) from -3 to -28 dB in 2dB steps  
4.10 The camera module shall feature an automatic mechanical IR cut-filter  
4.11 The camera module shall have a signal to noise ration of greater than 50dB  
4.12 The camera module shall use Internal / External (V-Lock) synchronisation  
4.13 The camera module shall have a lens that performs to F=4.1mm (WIDE) to 73.8mm (TELE), F1.4 to F3.0  
4.14 The camera module shall have an angle of view of 48° (WIDE end) to 2.8° (TELE end)  
4.15 The camera module shall have a shutter speed of 1/1 to 1/10,000s (22 steps) NTSC  
4.16 The camera module itself shall have up to 10 selectable settings that can be mapped to a preset on the remote keyboard, including shutter speed and colour control for ANPR applications

**4.0 The camera module within the PTZ unit shall meet or exceed the following design and performance specifications:**

**36x camera module**

- 4.17 The camera module shall feature a 1/4" EXview™ CCD  
4.18 The camera module shall be a true day/night unit  
4.19 The camera module shall switch from day mode (colour) to night mode (monochrome) via the remote keyboard.  
4.20 The camera module shall have a resolution of 470TVL (NTSC) / 460TVL (PAL)  
4.21 The camera module shall have a 36x optical zoom with 12x digital zoom  
4.22 The camera module shall have a minimum illumination sensitivity of 1.4 lux (1/60s NTSC, 1/50s PAL), 0.1 lux (1/4s NTSC, 1/3s PAL), 0.01 lux or less (1/4s NTSC, 1/3s PAL, ICR ON)  
4.23 The camera module shall have selectable on/off Backlight Compensation (BLC)  
4.24 The camera module shall have 16 steps aperture control  
4.25 The camera module shall have Automatic Gain Control (AGC) from -3 to -28 dB in 2dB steps  
4.26 The camera module shall feature an automatic mechanical IR cut-filter  
4.27 The camera module shall have a signal to noise ration of greater than 50dB  
4.28 The camera module shall use Internal / External (V-Lock) synchronisation  
4.29 The camera module shall have a lens that performs to F=3.4mm (WIDE) to 122.4mm (TELE), F1.6 to F4.5  
4.30 The camera module shall have an angle of view of 57.8° (WIDE end) to 1.7° (TELE end)

- 4.31 The camera module shall have a shutter speed of 1/4 to 1/10,000s (20 steps) NTSC, 1/3 to 1/10,000s (20 steps) PAL
- 4.32 The camera module itself shall have up to 10 selectable settings that can be mapped to a preset on the remote keyboard, including shutter speed and colour control for ANPR applications

**5.0 The unit shall have the following operational design and performance specifications**

- 5.1 The unit shall have 64 telemetry presets
- 5.2 The unit shall have preset titles of 20 characters for each preset
- 5.3 The unit shall have 6 tours, each with 32 preset positions
- 5.4 The unit shall have a random tour function
- 5.5 The unit shall have 64 sector titles, each with 20 characters
- 5.6 The unit shall have the ability to select a home position

**6.0 The unit shall have the following electrical design and performance specifications:**

- 6.1 Total power consumption of the standard camera with twin public address speakers shall be no more than 40W
- 6.2 The unit shall have available a Forward Vision power supply providing +18VDC from one of the following input voltages 12V DC to 24V DC, 24V AC, 115V AC & 240V AC
- 6.3 The camera unit shall be fitted with control PCBs including a control processor, voltage regulator, brushless motor drives and connectivity of ancillary items such as heaters, infrared illuminators and speakers

**7.0 The unit shall feature the following software specifications:**

- 7.1 The unit shall have the ability to operate with protocols other than Forward Vision's proprietary software, programmed prior to leaving the factory:
  - 7.1.1 The unit shall be compatible with American Dynamics protocol
  - 7.1.2 The unit shall be compatible with Ernitec protocol
  - 7.1.3 The unit shall be compatible with Kalatel protocol
  - 7.1.4 The unit shall be compatible with Molynx protocol
  - 7.1.5 The unit shall be compatible with Panasonic protocol
  - 7.1.6 The unit shall be compatible with Pelco P / Pelco D protocol
  - 7.1.7 The unit shall be compatible with Philips Bosch protocol
  - 7.1.8 The unit shall be compatible with VCL protocol
  - 7.1.9 The unit shall be compatible with Vicon protocol

**8.0 The unit shall have a range of options and accessories available for specific mounting and operational considerations:**

- 8.1 Suitable accessories shall be available for the unit to be mounted in an upright or inverted position either on a base, from a ceiling on at the corner of a structure
- 8.2 The unit shall have an option to fit a washer nozzle to the 4" PCD base
- 8.3 The unit shall have an optional integrated wiper with replaceable wiper blade
- 8.4 The unit shall have an optional safety chain
- 8.5 The unit shall have an optional 3D, scaling perspective privacy card with unlimited zones (which is housed in the camera head)
- 8.6 The unit shall have an optional 8 input alarm card (inc washer pump drive function (housed in the PSU)
- 8.7 The unit shall have an optional washer pump drive card (no alarm inputs) housed in the PSU
- 8.8 The unit shall have available power supplies providing +18VDC from one of the following input voltages 12V DC to 24V DC, 24V AC, 115V AC & 240VAC

**9.0 The unit shall have the following support information and equipment shipped with it:**

- 9.1 The unit shall have a comprehensive operation manual and installation manual provided by CD (English)
- 9.2 The unit shall come with a comprehensive quick start guide (English)